



High Definition Articulating VideoScope


6mm diameter camera with 240° articulating tip for best viewing angle

Easy one-hand operation of the articulating camera tip facilitates viewing in obstructed areas where standard camera tips cannot access. Images and videos are viewed on the large high resolution color display and can be stored in SD memory card (included)

Features:

- 6mm diameter camera head with 1m semi-rigid cable retains configured shape and 240° camera probe rotation
- 5.7" color LCD* TFT with high definition 640 x 480 VGA pixel resolution
- · Mini, high-resolution water-proof (IP57) camera head
- Rugged oil/chemical resistant and water/drop proof housing (IP67/2m)
- Non-slip ergonomic handles for ambidextrous use
- SD memory card included to store >15,000 images
- Video recording (up to 4 hours) with Voice annotation
- AV output for viewing images and video directly on a monitor
- · Video and images can be transferred to a PC via the SD card or USB output





B. HDV-WTX — Optional Wireless Transmitter transmits places up to 100ft (30m) away


Ordering Information:

240

HDV640High Definition Articulating VideoScope (6mm diameter/1m Semi-Rigid Cable)

Video Inspector Monitor (order camera head separately from accessories listed below) HDV600High Definition VideoScope (Monitor and hard carrying case only)

Uptional camera accessories
HDV-TX16mm Articulating VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable
HDV-WTX16mm Wireless Articulating VideoScope Camera Head w/Macro lens & 1m Semi-Rigid Cable
HDV-TX26mm Articulating VideoScope Camera Head w/Macro lens and 2m Semi-Rigid Cable
HDV-WTX26mm Wireless Articulating VideoScope Camera Head w/Macro lens & 2m Semi-Rigid Cable
HDV-4CAM-1FM4mm VideoScope Camera Head with Macro lens and 1m Flexible Cable
HDV-4CAM-5FM4mm VideoScope Camera Head with Macro lens and 5m Flexible Cable
HDV-5CAM-1FM5.5mm VideoScope Camera Head with Macro lens and 1m Flexible Cable
HDV-5CAM-3F5.5mm VideoScope Camera Head with long depth of field and 3m Flexible Cable
HDV-5CAM-3FM5.5mm VideoScope Camera Head with Macro lens and 3m Flexible Cable
HDV-5CAM-30FM5.5mm VideoScope Camera Head with Macro lens and 30m Flexible Cable
HDV-5CAM-10F5.5mm VideoScope Camera Head with long depth of field and 10m Flexible Cable
HDV-5CAM-1R5.8mm VideoScope Camera Head with long depth of field and 1m Semi-Rigid Cable
HDV-5CAM-1RM5.8mm VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable
HDV-5CAM-3R5.8mm VideoScope Camera Head with long depth of field & 3m Semi-Rigid Cable
HDV-5CAM-3RM5.8mm VideoScope Camera Head with Macro lens and 3m Semi-Rigid Cable
HDV-25CAM-10G25mm VideoScope Camera Head with long depth of field and 10m Fiberglass Cable
HDV-25CAM-30G25mm VideoScope Camera Head with long depth of field and 30m Fiberglass Cable
HDV-WTXWireless Transmitter
HDV-PCSpare Patch Cable for HDV Series
ADPTR-HDVReplacement AC Adaptor



HDV640 Includes:

· VideoScope, SD memory card, handset with articulating camera probe and 1m cable (Probe accessories: magnet, 45° mirror, and anti-snag tip), 3.7V rechargable Li-Polymer battery, patch cable, Universal AC adapter (110-240V, four plugs), USB and AV cables, and hard carrying case

Applications:

- Industrial Processing & Manufacturing
- Heavy Equipment
- HVAC/Boilers
- Aerospace
- · Government & Security
- Insurance
- · Mining and Aggregate
- Aviation AOG and FBO
- Power Generation
- **Building Inspection &**
- · PetroChem/Refineries
- Infrastructure



Camera probes with cable length greater than 3m will be coiled on a spool as shown on the left.



