

## GT SONIC-ST SERIES ULTRASONIC CLEANER



### Features:

1. Ultrasonic power :0-100% adjustable
2. Time setting:0-30min or 24 hours continuous working
3. Heating:20-80°C
4. Ultrasonic frequency: 28kHz or 40kHz
5. Material: 2mm thickness SUS304 tank for acid-proof.
6. Improved PCB design for stable and durable industrial use
7. More strong and uniform ultrasonic wave
8. With free lid and stainless steel SUS304 basket

### Application:

Aerospace,Marine, Railway,Automotive,Food and Beverage industry, Mining enterprise, Medical Devices,Moulding,Electronic industry (PCB,clock parts etc),Pharmaceutical Industry,Pneumatic Tools, Grinding and Polishing Shops, Optical and Glass Industry, Transport Technology and Precision Mechanics.

### Specification:

Model	Tank size	Unit size	Volume	Ultrasonic power	Ultrasonic frequency	Heating power	Heating temperature
	L×W×H(mm)	L×W×H(mm)	(L)	Normal (W)	(kHz)	(W)	(°C)
GT SONIC -ST13A/B	300×240×180	400×360×450	13	0-300	28&40	500	20-80
GT SONIC -ST36A/B	510×300×250	570×360×450	36	0-600		800	20-80