## **Digital Force Gauge**



Features

- \* High accuracy and high resolution.
- \* Digital display with no guessing or errors.
- \* With 4 measurement unit for selection, N, kg, lb, g.
- \* With peak value hold function.

Model: FM-207

## Applications

The digital force gauge is a kind of simple and convenient functional instrument for high-accuracy push force and pull force test. It is widely used in electronics, building hardware, textile, auto parts, ignition device such as lighter, fire fighting equipment, pen manufacturing, lock manufacturing, fishing gear, chemical, power machinery, scientific research institutions and other industries.

- \* Can memorize 99 groups of data.
- \* With 10 minutes auto power off and manual power off.
- \* Either alkaline battery Power supply or 6V DC power.
- \* Use USB cable or Bluetooth adapter for data output.

## Specification And Application Of Accessories

Accessory	Structure Diagram	Applications	
Pulling Hook		To hang tested objects when testing pulling force.	
Flat Tip		To test thrust of flat surface or convex surface.	
Cone Tip		To test thrust of flat surface, concave surface or circular hole.	
V-shaped Groove Tip		To test thrust of cylindrical surface or the edge of perpendicular planes.	
V-shaped Wedge Tip		To test thrust of flat surface or groove surface.	
Lengthening Connection Rod	Screw Rod Cap Nut	It is used in the situation when the measurement tip is not long enough.	

## Specifications

Model	FM-207-1K	FM-207-2K	FM-207-5K	FM-207-10K	FM-207-20K	FM-207-50K
Iviodei						
Force Range	±1kgf	±2kgf	±5kgf	±10kgf	±20kgf	±50kgf
	±1000gf	±2000gf	±5000gf			
	±9.8N	±19.6N	±49N	±98N	±196N	±490N
	$\pm 2.2 Lbf$	$\pm$ 4.4Lbf	$\pm 11Lbf$	$\pm 22 Lbf$	$\pm 44Lbf$	$\pm 110 Lbf$
Resolution	0.001kgf	0.001kgf	0.001kgf	0.001kgf	0.01kgf	0.01kgf
	1gf	1gf	1gf			
	0.01N	0.01N	0.01N	0.01N	0.1N	0.1N
	0.001Lbf	0.001Lbf	0.01Lbf	0.01Lbf	0.01Lbf	0.1Lbf
Accuracy	$\pm 0.2\%$ FS $\pm 1$ Digit					
Unit	kgf, gf, N, Lbf					
Measurement State	Peak Value Measurement, Real Time Measurement					
Display	2 Reversed 4 Digit LCD					
Power Off	10 Minutes Auto Power Off, Manual Power Off					
Backlight	Blue Backlight					
Safe Load	150%FS (Buzzer Alarm Over 110%FS)					
Data Output	USB, Bluetooth					
Power Supply	2x1.5 AA(UM-3) Battery or 6VDC Power Supply					
Operating	Temperature: 0~40°C					
Conditions	Humidity: <80%					
Surrounding	No Vibration Source or Corrosive Medium Around					
Weight	390 g					
Size	211x80x36 mm					

Accessories

	Digital Fores Course				
	Digital Force Gauge				
Standard Accessories	Pulling Hook				
	Flat Tip				
	Cone Tip				
	V-shaped Groove Tip				
	V-shaped Wedge Tip				
	Lengthening Connection Rod	Screw Rod			
		Cap Nut			
	Manual				
	Carrying Case				
	CD				
Optional Accessories	USB Data Cable				
	Bluetooth Adapter				
	Power Adapter				
	Force Gauge Stand				