



testo 605-H1 • testo 405-V1 • testo 905-T1/-T2

## Pocket-size professional technology



Swivel head: reading visible from every angle



Fits inside every pocket



Easy-to-read display



Integrated protection cap

m/s

°C

%RH

°C

m/s

°C

%RH

## Your benefits when you use Testo sticks

- Swivel, locking display head – the display can always be read.
- Accurate “professional sensors” available for the first time in low cost stick measuring instruments.
- All instruments can be operated using one button.
- Large, easy-to-read display.
- Attached cap to protect humidity and velocity sensors.
- Battery can be easily changed by user.
- Multi-function clip supplied with °C, %RH and m/s sticks.
- Duct holder supplied with %RH and m/s sticks.

### Humidity measurement stick




**testo 605-H1** The humidity measurement stick with the trick. Small, compact and accurate. It can be attached to your breast pocket via the push-on clip.

#### Advantages:

- Worldwide patented, accurate and long-term stable Testo humidity sensor.
- Integrated dew point calculation
- Pocket-size
- User-friendly operation
- Sensor not affected by water
- Auto OFF function

<b>Measuring range:</b>	5 to 95 %RH -20 to +70 °C
<b>Parameters:</b>	%RH/°C/°F
<b>Resolution:</b>	0.1 %RH/ 0.1 °C
<b>Accuracy:</b>	±3 %RH / ±0.5 °C
<b>Ambient temp.:</b>	0 to +50 °C
<b>Storage temp.:</b>	-20 to +70 °C
<b>Battery type:</b>	3 V button cell (CR2032)
<b>Battery lifetime</b>	Approx. 200 h
<b>Probe stem:</b>	Ø 12 mm, L.: 125 mm
<b>Auto OFF:</b>	Approx. 10 minutes
<b>Warranty:</b>	2 years

### Velocity measurement stick




**testo 405-V1** is the first mini anemometer in this price range which can measure air velocity **and** volume flow.

#### Advantages:

- Measures in ducts and duct outlets
- Pocket-size
- With a length of 300 mm when extended also suitable for larger duct diameters
- User-friendly operation
- Auto OFF function

<b>Measuring range:</b>	0 to 5 m/s at -20 to 0 °C 0 to 10 m/s at 0 to +50 °C 0 to 99,990 m³/h -20 to +50 °C
<b>Resolution:</b>	±0.01 m/s / ±0.1 °C
<b>Accuracy:</b>	±5 % of m.v. ±0.10 m/s (up to 2 m/s) ±5 % of m.v. ±0.30 m/s (over 2 m/s) ±0.5 °C
<b>Ambient temp.:</b>	0 to +50 °C
<b>Storage temp.:</b>	-20 to +70 °C
<b>Battery type:</b>	3 x micro (AAA)
<b>Battery lifetime</b>	≈ 750 meas. à 2 min.
<b>Probe stem:</b>	Ø 12/16 mm, length: approx. 300 mm
<b>Auto OFF:</b>	Approx. 5 min.
<b>Warranty:</b>	2 years

### Temperature measurement stick



**testo 905-T1** is ideal for super-quick measured results in liquids, air and in soft or powdery substances.

#### Advantages:

- Quick measurement
- Professional industrial sensor (type K thermocouple)
- High temperature measurement, short-term to +500 °C
- User-friendly operation and battery change
- Auto OFF function

### Surface temperature measurement stick



**testo 905-T2** The sprung, wide thermocouple measuring head, type K, guarantees a very quick reaction time and a high accuracy level by placing the probe flat on the uneven surface.

#### Advantages

- Super quick measurement
- User-friendly operation
- Practical and compact
- Auto OFF function

<b>Measuring range</b>	-50 to +350 °C short-term to +500 °C
<b>Parameters:</b>	°C / °F
<b>Resolution:</b>	0.1 °C
<b>Accuracy of 905-T1</b>	±1 °C (to +100 °C) ±1 % of m.v.(rem. range)
<b>905-T2</b>	±1 °C ±1 % of m.v.
<b>Ambient temp.:</b>	0 to +40 °C
<b>Storage temp.:</b>	-20 to +70 °C
<b>Response time t<sub>99</sub> :</b>	
<b>905-T1</b>	Approx 10 s (in water)
<b>905-T2</b>	Approx. 5 s
<b>Battery type:</b>	3 V button cell (CR2032)
<b>Battery lifetime</b>	Approx. 150 h
<b>Probe stem:</b>	
<b>905-T1</b>	Ø 3 mm / 200 mm long
<b>905-T2</b>	Ø 12 mm / 150 mm long
<b>Auto OFF:</b>	Approx. 10 min
<b>Warranty</b>	2 years

## You can order by fax, post or telephone!

Simply copy this page as often as required, complete the details and return to us by fax or post. Don't forget to include your name and address.

Qty.	Ordering data	Part no.
	<b>testo 605-H1</b> humidity measurement stick , incl. multi-function clip, duct holder, battery, instruction manual	0560.6051
	<b>testo 405-V1</b> velocity measurement stick , incl. multi-function clip, duct holder, battery, Instruction manual	0560.4051
	<b>testo 905-T1</b> temperature measurement stick , incl. multi-function clip, battery, Instruction manual	0560.9051
	<b>testo 905-T2</b> surface temperature measurement stick , with crossband probe, incl. multi-function clip, battery, Instruction manual	0560.9052
	<b>ISO calibration certificate</b>	On request

Subject to change without notice.

Name _____	Address _____
Company _____	_____
Department _____	Date, Signature _____